(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 29 December 2004 (29.12.2004)

(10) International Publication Number WO 2004/114513 A1

(51) International Patent Classification?: B60N 2/56, B60H L/24

(21) International Application Number:

PCT/SE2004/001031

(22) International Filing Date:

24 June 2004 (24.06.2004)

(25) Filing Language:

Swedish

(26) Publication Language:

English

(30) Priority Data: 0301871-0

26 June 2003 (26.06.2003) SE

(71) Applicant (for all designated States except US): KONGS-BERG AUTOMOTIVE AB [SE/SE]; Box 504, S-565 28 Mulisjö (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): FRISTEDT, Tommy [SE/SE]; Stockeryd, S-560 25 Bottnaryd (SE).

(74) Agent: ALBIHNS GÖTEBORG AB; Box 142, S-402 22 Göteborg (SB).

H02P 5/17, (81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM. TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,


> (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FL, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND ARRANGEMENT FOR CONTROL OF DIRECT CURRENT MOTOR



(57) Abstract: The present invention relates to a method for control of a direct current motor (30) in one or several fan units (43, 20, 21) and comprising a few publishments of the present invention of the present invent 21), each comprising a fan, which method comprises: generation of a control signal from a first control unit (22) which is external in relation to the said fan unit (43, 20, 21); transmission of the said control signal to the said fan unit (43, 20, 21); reception of the transmitted control signal in the said fan unit (43, 20, 21); interpretation of the said control signal in a second control unit (26) which is arranged in association with the said fan unit (43, 20, 21); and generation, in the said second control unit (26), of a supply signal for the said direct current motor (30), on the basis of the control signal generated by the first control unit (22) and received in the fan unit and on the basis of a supply voltage. According to the invention, the method comprises transmission of the control signal together with the supply voltage over a shared communication link (44), with the control signal being superposed on the supply voltage. The invention also relates to an arrangement for such control. By means of the invention, improved control is obtained of a motor that can be utilized in a ventilated seat in a vehicle.